



ECRF COLD BOND CEMENT & HARDENER



Photo shows 800 ml size with 35 gr hardener.



ECRF is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- ECRF is an ethyl acetate based chloroprene cement that is available in pint, quart, gallon and drum sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons

ECRF CEMENT PROPERTIES

Colour	Black
Weight / Gallon	.700 kg
Pot Life	4 Hours @ 70°F (22°C)
Working Temperature	-10°F to 180°F
Shelf Life	24 months in cool, dark location

DESCRIPTION	Product Code	Hardener	Volume		Weight		Coverage	
			Gal	Liter	lbs	kg	ft ²	m ²
ECRF Pint	CC-ECRF-001	1 - 20 gr	0.12	0.4	0.8	0.35	30	2.8
ECRF Quart	CC-ECRF-002	1 - 35 gr	0.20	0.8	1.5	0.7	60	5.6
ECRF Gallon	CC-ECRF-010	5 - 35 gr	1	4	7.7	3.5	300	28
ECRF Drum	CC-ECRF-200	250 - 35 gr	50	200	386	175	15,000	1400

DESCRIPTION	Product Code	Gram
20 gr Hardener	CH-ECRF-020	20
35 gr Hardener	CH-ECRF-035	35



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011