



FABRIC BELT COVER STOCK



Fabric Belt Cover Stock is an uncured rubber for hot vulcanized belt splicing. It is designed for use as a cover rubber replacement material in splicing fabric conveyor belts. The material is designed to bond to the cured cover rubber in all standard grades of fabric conveyor belts.

FEATURES:

- Enhances working life of fabric splices
- Improves wear and tearing resistance on conveyor belt splices
- Eliminates surface contamination (normal application) with double sided poly
- Uses poly color coding system to ID compound
- For Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. - Neoprene (CR) rubber belt splices

PROPERTIES

Base Polymer	NR Rubber
Rubber Color	Black
Poly Liner Color	White (double sided)
Specific Gravity	1.15 - 1.21
Hardness	65 - 75 Shore A
Tensile	2500 - 3000 psi
Elongation	300 - 500% (at break)
Shelf Life	6 months at 70°F or 12 months at 50°F

PRODUCT CODE	Poly Color (both sides)	Thickness/Gauge			Width		Length		Roll Weight	
		fac	in	mm	in	m	ft	m	kg	lb
AA-FBC-031	White	1/32	.031	.8	20	.5	49	15	7	15.3
AA-FBC-062	White	1/16	.063	1.6	20	.5	49	15	13.9	30.6
AA-FBC-093	White	3/32	.090	2.3	20	.5	33	10	13.3	29.3
AA-FBC-125	White	1/8	.126	3.2	20	.5	26	8	14.8	32.7
AA-FBC-156	White	5/32	.153	3.9	20	.5	26	8	18.1	39.8
AA-FBC-187	White	3/16	.185	4.7	20	.5	16	5	13.6	30
AA-FBC-218	White	7/32	.216	5.5	20	.5	16	5	16	35.1
AA-FBC-250	White	1/4	.248	6.3	20	.5	16	5	18.3	40.2



Note: The above data is based on extensive testing and represents standard values. Shaw Almix Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011