



FUSIONLAGG OMD



FusionLagg OMD (Orange Mini Diamond) is a small profile pulley lagging, ideal for driven pulleys with medium to low tensions and belt ratings.

FEATURES:

- Excellent coefficient of friction in wet or muddy installations
- Features the Fusion bonding layer technology for superior adhesion to the pulley surface
- A natural rubber compound with high abrasion resistance and water in fine shedding capability
- The moulded mini diamond pattern offers exceptional grip and wear resistance
- Ideal for driven head or tail pulleys requiring a medium profile and particularly suited for wet applications

PROPERTIES			
Colour	Orange		
Elastomer	NR		
Tensile Strength	19 Mpa	DIN 53504	
Elongation at Break	600%	DIN 53504	
Density	1.08 g / cm ³	DIN 35050	
Hardness	48 Shore A	DIN 53505	
Abrasion Resistance	260 mm ³	DIN 53516	
Groove Dimensions	4 mm x 3 mm	3/16" x 1/8"	
Diamond Dimension	40 mm x 20 mm	1" x 3/4"	

PRODUCT CODE	Thickness/Gauge			Width		Length		Weight	
	Frac	in	mm	in	mm	ft	m	lbs	kg
CFL-OMD-650	1/4	.25	7	59.5	1500	50	15.25	150	68



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011