




FUSIONWEAR 60



FusionWear 60 is a specially blended tough rubber compound, ideal in the handling of coarse materials where impact and abrasion wear exist.

FEATURES:

- High resilience and resistance to permanent deformation makes FusionWear 60 the ideal product for wear problems in the handling of large particle coarse ore
- Offers excellent flexibility and enhances the movement of material fines, eliminating caking or buildup of product fines when mixed with larger particles
- Exceptional wear and tear resistance
- Positive noise reduction
- Optimum performance & reliability

PROPERTIES

Colour	Black	
Elastomer	NR / BR	
Tensile Strength	20 Mpa	DIN 53504
Elongation at Break	450%	DIN 53504
Density	1.10 g / cm ³	DIN 53505
Hardness	60 (+/-5) Shore	DIN 53505
Abrasion Resistance	<120 mm ³	DIN 53516

PRODUCT CODE	Thickness/Gauge		Width		Length		Roll Weight	
	in	mm	in	mm	ft	m	lbs	kg
CFW-60SB-1250	1/8	3	59	1500	50	15.25	182	83
CFW-60SB-2550	1/4	6	59	1500	50	15.25	191	87
CFW-60SB-3750	3/8	10	59	1500	50	15.25	612	278
CFW-60SB-5050	1/2	12	59	1500	50	15.25	732	322
CFW-60SB-6250	5/8	15	59	1500	50	15.25	917	416
CFW-60SB-7550	3/4	20	59	1500	50	15.25	1215	551
CFW-60SB-1050	1	25	59	1500	50	15.25	1520	690
CFW-60SB-2050	2	50	59	1500	16.5	5.0	506	230



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011