



CRF COLD BOND CEMENT & HARDENER



Photo shows 1 kg with 35 gr hardener.

CRF is the ideal cement when bonding rubber to rubber, and is ideal for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- Long pot life
- Can be used on rubber, fabric, wood, fiberglass, concrete, urethane and steel
- Is a Chloroprene based cement available in pint, quart, gallon and drum

CRF CEMENT PROPERTIES	
Colour	Dark Grey
Weight / Gallon	11 lbs or 5 kg
Pot Life	4 Hours @ 70°F (22°C)
Working Temperature	-40°F to 180°F
Shelf Life	2 years in cool, dark location

DESCRIPTION	Product Code	Hardener	Weight		Coverage	
			lbs	kg	ft ²	m ²
CRF Pint	CC-CRF-001	1 - 20 gr	1.1	0.5	20	1.9
CRF Quart	CC-CRF-002	1 - 35 gr	2.2	1	40	3.7
CRF Gallon	CC-CRF-010	5 - 35 gr	11	5	200	18.6
CRF Drum	CC-CRF-200	290 - 35 gr	640	290	11,600	1,078

DESCRIPTION	Product Code	Gram
20 gr Hardener	CH-CRF-020	20
35 gr Hardener	CH-CRF-035	35



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011