



ECRF COLD BOND CEMENT & HARDENER



Photo shows 800 ml size with 35 gr hardener.



ECRF is the ideal cement for conveyor belt repair and splicing, and is excellent for use on wood, fiberglass, concrete, urethane, steel, rubber and fabric.

FEATURES:

- ECRF is an ethyl acetate based chloroprene cement that is available in pint, quart, gallon and drum sizes
- Free of chlorinated hydrocarbons
- High initial and permanent adhesion
- Easy to process
- Offers higher threshold limit values than for chlorinated hydrocarbons

ECRF CEMENT PROPERTIES

| | |
|---------------------|----------------------------------|
| Colour | Black |
| Weight / Gallon | .700 kg |
| Pot Life | 4 Hours @ 70°F (22°C) |
| Working Temperature | -10°F to 180°F |
| Shelf Life | 24 months in cool, dark location |

| DESCRIPTION | Product Code | Hardener | Volume | | Weight | | Coverage | |
|-------------|--------------|-------------|--------|-------|--------|------|-----------------|----------------|
| | | | Gal | Liter | lbs | kg | ft ² | m ² |
| ECRF Pint | CC-ECRF-001 | 1 - 20 gr | 0.12 | 0.4 | 0.8 | 0.35 | 30 | 2.8 |
| ECRF Quart | CC-ECRF-002 | 1 - 35 gr | 0.20 | 0.8 | 1.5 | 0.7 | 60 | 5.6 |
| ECRF Gallon | CC-ECRF-010 | 5 - 35 gr | 1 | 4 | 7.7 | 3.5 | 300 | 28 |
| ECRF Drum | CC-ECRF-200 | 250 - 35 gr | 50 | 200 | 386 | 175 | 15,000 | 1400 |

| DESCRIPTION | Product Code | Gram |
|----------------|--------------|------|
| 20 gr Hardener | CH-ECRF-020 | 20 |
| 35 gr Hardener | CH-ECRF-035 | 35 |



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011