



HOT SPLICE CEMENT



Photo shows 1 quart.

Hot Splice HC1 adhesive is a one part cement for hot vulcanized belt splicing. It is designed for use as a tackifying agent for cured to uncured rubber materials.

FEATURES:

- Enhances vulcanization of belt splices
- Adds building tack to the uncured splice materials and conveyor belt splice
- Brushable consistency for ease of application and good penetration
- HC1 adhesive can be used over a variety of adhesive systems such as Fabric Primer and Steel Cord Primer
- Use for Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. - Neoprene (CR) rubber belt splices

PROPERTIES	
Colour	Black
Base	NR / SBR Rubber
Solids (wt.)	13 - 15%
Solvents	Toluene (60%), Ethyl Acetate (15%), Heptane (10%)
Calculated Coverage	144 sf / gal /mil
Flash Point	Closed Cup 20°F
Shelf Life	6 months at 70°F or 12 months at 50°F

PRODUCT CODE	Label Colour	Unit Volume		Product Weight	
		Gal	litre	kg	lb
AA-HC1-Q	Gray	Quart	.95	.7	1.54
AA-HC1-G	Gray	Gallon	3.78	3	6.6
AA-HC1-5G	Gray	5 Gallon Pail	18.90	14.5	31.9
AA-HC1-55G	Gray	54 Gallon Drum	205	170	374



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011