



HOT SPLICE STEEL CORD PRIMER



Photo shows 1 quart.

Hot Splice Steel Cord Primer is a one part coating for non-rubberized cords that enhances adhesions in hot vulcanized steel cord belt splicing. It is designed for use as a reactive bonding agent between metal surfaces and uncured splice materials.

FEATURES:

- HC1 splice cement can be applied directly over Steel Cord Primer as tack cement.
- Almex Steel Cord Primer has excellent brushable consistency for ease of application onto the cords
- For Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. - Neoprene (CR) rubber belt splices

PROPERTIES	
Colour	Black
Base	Mixture of polymers
Solids (wt.)	20 - 25%
Solvent	Xylene
Calculated Coverage	144 sf /gal / mil
Flash Point	Closed Cup 79°F
Shelf Life	6 months at 70°F or 12 months at 50°F

PRODUCT CODE	Label Colour	Unit Volume		Product Weight	
		Gal	litre	kg	lb
AA-HSP-Q	Blue	Quart	.95	.95	2.09



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011