



# RM RUBBER TO METAL PRIMER



Photo shows 800 ml.

An ideal Metal Primer for use in rubber tanks or chute lining, pulley lagging, and all applications where a bond to metal requires enhancement.

### FEATURES:

- As an interface between rubber and metal, RM offers high bond strengths between both surfaces
- Unlike zinc based primers, RM utilizes polymers and organic compounds to achieve a high strength bond
- Mixture of polymers, organic compounds and mineral fillers dissolved or dispersed in an organic solvent system
- Can be used on steel, aluminum, titanium, wood and other substrates
- Can be applied with a brush, roller or spray

### PROPERTIES

Formula	M.I.B.K. / M.E.K. / Xylene
Colour	Grey
Flash point	42°F
Shelf Life	1 year from date of manufacture (70 - 80°F)

DESCRIPTION	Product Code	Volume		Weight		Coverage	
		Gal	Liter	lbs	kg	ft <sup>2</sup>	m <sup>2</sup>
<b>Rubber/Metal Primer</b>							
Primer Quart	CP-RM-Q	1 qt	0.8	1.5	0.7	147	13.7
Primer Gallon	CP-RM-G	1 gal	3.78	7.7	3.5	588	54.9



**Note:** The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011