



WCRF COLD BOND CEMENT & HARDENER



Photo shows 1 kg with 35 gr hardener bottle.

WCRF is formulated for use with food grade conveyor belt and rubber to metal bonding and is ideal for fabrication, including T-Cleat and V-guide attachment to food belts.

FEATURES:

- Long pot life
- For use on rubber, fabric, wood, fiberglass, concrete, urethane and steel
- Is a Chloroprene based cement available in pint, quart, gallon and drum sizes
- Environmentally friendly

WCRF CEMENT PROPERTIES	
Colour	White
Weight / Gallon	11 lbs or 5 kg
Pot Life	4 Hours @ 70°F (22°C)
Working Temperature	-40°F to 180°F
Shelf Life	2 years in cool, dark location

DESCRIPTION	Product Code	Hardener	Weight		Coverage	
			lbs	kg	ft ²	m
WCRF Pint	CC-WCRF-001	1 - 20 gr	1.1	1/2	20	1.9
WCRF Quart	CC-WCRF-002	1 - 35 gr	2.2	1	40	3.7
WCRF Gallon	CC-WCRF-010	5 - 35 gr	11	5	200	18.6
WCRF Drum	CC-WCRF-600	290 - 35 gr	640	290	11600	1078

DESCRIPTION	Product Code	Gram
20 gr Hardener	CH-WCRF-020	20
35 gr Hardener	CH-WCRF-035	35



Note: The above data is based on extensive testing and represents standard values. Shaw Almex Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.

Updated: Dec. 2011